



Material Safety Data Sheet

SAKSHI GARD 430-RAL 6038

1. Product and company identification

Product name	SAKSHI GARD 430- Base, PART A- RAL 6038
	EPOXY FINISH PAINT
Intended use	Refer technical data sheet
	For Industrial use only
Application method	Brush/Roller/Spray/ Pouring
Company name	SAKSHI COATING PVT.LTD.
	Gala No.2, Opp. Mhatre Compound, Gothivali Village Road Rabale, Navi Mumbai – 400 701, India
Telephone No.	+91 22 6561 6751
E-mail	sakshihitech@gmail.com
Website	www.sakshihitech.com

2. Composition/Information on ingredients

This product contains the following substances that present a health hazard within the meaning of the Dangerous Substances Directive and Chemical Regulation:

Ingredient	CAS No	Concentration Range%
Epoxy Resin	025068-38-6	15-25
Xylene (o-,m-,p-)	001330-20-7	10-25
Barium Sulfate	007727-43-7	10-20
Titanium Dioxide	013463-67-7	01-10
Pigment Green -7	14832-14-5	05-10
Ph.Blue Pigment	1328-53-6	01-02
Carbon black HF	001333-86-4	00-01
Solvent Naphtha (Petroleum)	064742-95-6	0-5
Light Aromatic		
1-Methoxy-2-Propanol	000107-98-2	2.5-10
Organoclay	068911-87-5	1-2.5

Total may not equal 100%. The rest of the ingredients in this product are classified as non-hazardous.

3. Hazard identification of the product



Warning

Flammable

Harmful by inhalation, in contact with skin and if swallowed

Irritating to eyes and skin



Material Safety Data Sheet

SAKSHI GARD 430-RAL 6038

4. First aid measures

General

In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration.

If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eye Contact

Irrigate copiously with clean fresh water for at least 10 minutes, holding the eyelids apart and seek medical attention.

Skin Contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognised skin cleanser. Do NOT use solvents or thinners.

Ingestion

If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

5. Fire-fighting measures

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray.

Do not use – water jet.

Note: Fire will produce dense black smoke. Decomposition products may be hazardous to health. Avoid exposure and use breathing apparatus as appropriate.

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

6. Accidental release measures

Remove sources of ignition, do not turn lights or unprotected electrical equipment on or off. In case of a major spill or spillage in a confined space evacuate the area and check that solvent vapour levels are below the Lower Explosive Limit before re-entering.

Ventilate the area and avoid breathing vapours. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, vermiculite. Place in closed containers outside buildings and dispose of according to relevant State regulations.

Clean preferably with a detergent. Do not use solvents.

Do not allow spills to enter drains and watercourses.

If drains, sewers, streams or lakes are contaminated, inform the relevant environmental protection agency.

Empty containers may contain product residues, including flammable or explosive vapours. Do not cut, puncture or weld on or near containers.



Material Safety Data Sheet

SAKSHI GARD 430-RAL 6038

7. Handling and storage

Handling

This coating contains solvents. Solvent vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Areas of storage, preparation and application should be ventilated to prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the occupational exposure limits.

In Storage

Handle containers carefully to prevent damage and spillage. Naked flames and smoking should not be permitted in storage areas. It is recommended that fork lift trucks and electrical equipment are protected to the appropriate standard.

In Use

Avoid skin and eye contact. Avoid inhalation of vapours and spray mists. Use personal protection as shown in section 8. Smoking, eating and drinking should be prohibited in all preparation and application areas. Never use pressure to empty container; containers are not pressure vessels. All sources of ignition (hot surfaces, sparks, open flames etc) should be excluded from areas of preparation and application. All electrical equipment (including torches) should be protected to the appropriate standard. The product may charge electrostatically. Always use earthing leads when pouring solvents and transferring products. Operators should wear clothing which does not generate static electricity (at least 60% natural fibre) and antistatic footwear; floors should be of conducting type.

Storage

Store in a well ventilated, dry place away from sources of heat and direct sunlight. Store on concrete or other impervious floor, preferably with bunding to contain any spillage. Do not stack more than 3 pallets high. Keep container tightly closed. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in the original container or one of the same material. Prevent unauthorised access.

8. Exposure controls and personal protection

Engineering measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapour below occupational exposure limits suitable respiratory protection must be worn.

Exposure Limits

The following occupational exposure limits have been established by the Health and Safety Department.

Material	Short term (15 min avg)		Long term (8hr time weighted average)	
	ppm	mg/M ³	ppm	mg/M ³
Xylene (o-,m-,p-)	150	651	100	434
1-Methoxy-2-Propanol	150	553	100	369
Barium Sulfate	----	----	----	10
Titanium Dioxide	----	----	----	10
(P) Peak exposure limit	(Cat1) Category 1 – established human carcinogen			
(R) Suppliers recommended limit	(Cat2) Category 2 – probable human carcinogen			
(Sk) There is a risk of absorption through broken skin	(Cat3) Category 3 – substances suspected of having carcinogenic potential			
(Sen) Sensitiser				



Material Safety Data Sheet

SAKSHI GARD 430-RAL 6038

8. Exposure controls and personal protection

Personal Protection

Respiratory Protection

When concentrations exceed the exposure limits shown above, workers must wear appropriate approved respirators. Provision of other controls such as exhaust ventilation should be considered if practical.

Eye Protection

Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the splash of liquids. Eyewear should comply with an approved standard.

Wear a full face shield if mixing or pouring operations pose a risk of splashes.

An eye wash station is suggested as a good working place practice.

Hand Protection

Gloves of an appropriate material should be worn during mixing and application.

Skin Protection

Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. Barrier creams may help protect areas which are difficult to cover such as the face and neck. They should however not be applied once exposure has occurred. Petroleum jelly based types such as Vaseline should not be used. All parts of the body should be washed after contact.

Hygiene measures: Avoid contact with skin, eyes and clothing.



9. Physical and chemical properties

Physical State	Liquid
Colour	RAL 6038
Flash Point (deg C)	27
Specific Gravity @ 30°C	1.40±0.05
Vapour Density	Heavier than air
Lower Explosive Limit%	0.8
R.A.Q. to ventilate to the 10% of LEL (M3/l)	139
Solubility in Water	Immiscible
Viscosity (cST)	N/A
Odour	Smell of solvent

10. Stability and reactivity

Stable under recommended storage and handling conditions. When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide, carbon dioxide, oxides of nitrogen and smoke.

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid possible exothermic reactions.



Material Safety Data Sheet

SAKSHI GARD 430-RAL 6038

11. Toxicological information

There are no data available on the product itself.

Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through skin.

Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

12. Ecological information

There are no data available on the product itself.

The product should not be allowed to enter drains or water courses.

The product does not contain any substances classified as dangerous for the environment.

13. Disposal considerations

Do not allow any drains or water courses. Wastes and empty containers should be disposed of in accordance with the Pollution Act and Environmental Protection Act.

14. Transport information

Transport only in accordance with the following regulations:

ADR/RID

1263, Paint, 3, III, 3[Y]

IMDG reference

Class/Div

3

Subsidiary Class

Proper Shipping name

Paint

UN No

1263

Ems

F-E, S-E

Packaging Group

III

Marine Pollutant

No

ICAO/IATA

Shipping Name

Paint

Class

3

UN No

1263

Packaging Group

III



Material Safety Data Sheet

SAKSHI GARD 430-RAL 6038

15. Regulatory information

The product complies with local Pollution Act, Environmental Protection Act and regulations.

16. Other information

Sources of key data used to compile Material safety data sheets of the ingredients.

Data sheet:

Prepared by: Safety, Health and Environmental Department, SAKSHI COATING PVT.LTD

Revision Date: 01/02/2019

Reason for revision: New Format.

The information on this MSDS is based upon the present state of our knowledge and on current national laws. The product should not be used for purposes other than shown in the product data sheet without first obtaining written advice.

It is always the responsibility of the user to take all necessary steps to meet the demands of applicable legislation. Copies of product data sheet are available from SAKSHI COATING PVT.LTD., on request.