



Material Safety Data Sheet

SAKSHI THANE 530, RAL 7038

1. Product and company identification

Product name SAKSHITHANE 530,-RAL 7038
BASE, - PART A,
 Intended use Refer technical data sheet
 For Industrial use only
 Application method Brush/Roller/Spray
 Company name **SAKSHI COATING PVT. LTD.**
 Unit No.2, Opp. Mhatre Compound,
 Gothivali Road, Rabble.
 Navi Mumbai, INDIA
 400701.
 Telephone No. + 91 22 65616751
 Mobile - +91 09867143094
 Email- sakshihitech@gmail.com

2. Composition/Information on ingredients

This product contains the following substances that present a health hazard within the meaning of the Dangerous Substances Directive and Chemical Regulation:

Ingredient	CAS No	Concentration Range%
Acrylic Resin	Not Available	25-50
Xylene	001330-20-7	10-20
1-Methoxy-2-propyl acetate	000108-65-6	2.5-10
Calcium carbonates	001317-65-3	10-15
Titanium Dioxide	013463-67-7	05-10
Ph.Blue Pigment	1328-53-6	00-01
Carbon black HF	001333-86-4	00-01
Castor oil	008001-79-4	2.5-5
Dibutyltin dilaurate	0000077-58-7	<1

Total may not equal 100%. The rest of the ingredients in this product are classified as non-hazardous.

3. Hazard identification of the product



Flammable
 Harmful by inhalation, in contact with skin and if swallowed
 Irritating to eyes and skin



Material Safety Data Sheet

SAKSHI THANE 530, RAL 7038

4. First aid measures

General

In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.

Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eye Contact

Irrigate copiously with clean fresh water for at least 10 minutes, holding the eyelids apart and seek medical attention.

Skin Contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognised skin cleanser. Do NOT use solvents or thinners.

Ingestion

If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

5. Fire-fighting measures

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray.

Do not use – water jet.

Note: Fire will produce dense black smoke. Decomposition products may be hazardous to health. Avoid exposure and use breathing apparatus as appropriate.

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

6. Accidental release measures

Remove sources of ignition; do not turn lights or unprotected electrical equipment on or off. In case of a major spill or spillage in a confined space evacuate the area and check that solvent vapour levels are below the Lower Explosive Limit before re-entering.

Ventilate the area and avoid breathing vapours. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to relevant State regulations.

Clean preferably with a detergent. Do not use solvents.

Do not allow spills to enter drains and watercourses.

If drains, sewers, streams or lakes are contaminated, inform the relevant environmental protection agency.

Empty containers may contain product residues, including flammable or explosive vapours. Do not cut, puncture or weld on or near containers.



Material Safety Data Sheet

SAKSHI THANE 530, RAL 7038

7. Handling and storage

Handling

This coating contains solvents. Solvent vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Areas of storage, preparation and application should be ventilated to prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the occupational exposure limits.

In Storage

Handle containers carefully to prevent damage and spillage.

Naked flames and smoking should not be permitted in storage areas. It is recommended that fork lift trucks and electrical equipment are protected to the appropriate standard.

In Use

Avoid skin and eye contact. Avoid inhalation of vapours and spray mists. Use personal protection as shown in section 8.

Smoking, eating and drinking should be prohibited in all preparation and application areas.

Never use pressure to empty container; containers are not pressure vessels.

All sources of ignition (hot surfaces, sparks, open flames etc) should be excluded from areas of preparation and application. All electrical equipment (including torches) should be protected to the appropriate standard.

The product may charge electrostatic ally. Always use earthing leads when pouring solvents and transferring products. Operators should wear clothing which does not generate static electricity (at least 60% natural fibre) and antistatic footwear; floors should be of conducting type.

Storage

Store in a well ventilated, dry place away from sources of heat and direct sunlight.

Store on concrete or other impervious floor, preferably with bunding to contain any spillage. Do not stack more than 3 pallets high.

Keep container tightly closed. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in the original container or one of the same materials.

Prevent unauthorised access.

8. Exposure controls and personal protection

Engineering measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapour below occupational exposure limits suitable respiratory protection must be worn.

Exposure Limits

The following occupational exposure limits have been established by the Health and Safety Department.

Material	Short term (15 min avg)		Long term (8hr time weighted average)	
	ppm	mg/M ³	ppm	mg/M ³
Xylene	100	441	50	220
1, 2,4Trimethyl Benzene	25	125		
1-Methoxy-2-propyl acetate	100	360		

(P) Peak exposure limit

(Cat1) Category 1 – established human carcinogen

(R) Suppliers recommended limit

(Cat2) Category 2 – probable human carcinogen

(Sk) There is a risk of absorption through broken skin

(Cat3) Category 3 – substances suspected of having

(Sen) Sensitiser

carcinogenic potential



Material Safety Data Sheet

SAKSHI THANE 530, RAL 7038

8. Exposure controls and personal protection

Personal Protection

Respiratory Protection

When concentrations exceed the exposure limits shown above, workers must wear appropriate approved respirators. Provision of other controls such as exhaust ventilation should be considered if practical.

Eye Protection

Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the splash of liquids. Eyewear should comply with an approved standard.

Wear a full face shield if mixing or pouring operations pose a risk of splashes.

An eye wash station is suggested as a good working place practice.

Hand Protection

Gloves of an appropriate material should be worn during mixing and application.

Skin Protection

Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. Barrier creams may help protect areas which are difficult to cover such as the face and neck. They should however not be applied once exposure has occurred. Petroleum jelly based types such as Vaseline should not be used. All parts of the body should be washed after contact.

9. Physical and chemical properties

Physical State	Liquid
Colour	RAL 7038
Flash Point (deg C)	34
Specific Gravity @ 30deg C	1.10±0.03
Vapour Density	Heavier than air
Lower Explosive Limit%	0.8
Solubility in Water	Immiscible
Viscosity by FC B4 @ 30 deg C	NA
Odour	Smell of solvent

10. Stability and reactivity

Stable under recommended storage and handling conditions. When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide, carbon dioxide, oxides of nitrogen and smoke.

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid possible exothermic reactions.



Material Safety Data Sheet

SAKSHI THANE 530, RAL 7038

11. Toxicological information

There are no data available on the product itself.

Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

12. Ecological information

There are no data available on the product itself.

The product should not be allowed to enter drains or water courses.

The product does not contain any substances classified as dangerous for the environment.

13. Disposal considerations

Do not allow any drains or water courses. Wastes and empty containers should be disposed of in accordance with the Pollution Act and Environmental Protection Act.

14. Transport information

Transport only in accordance with the following regulations:

ADR/RID 1263, Paint, 3, III, 3[Y]

IMDG reference	Class/Div	3	Subsidiary Class
	Proper Shipping name	Paint	
	UN No	1263	MFAG 310
	Ems	3-05	
	Packaging Group	III	
	Marine Pollutant	No	

ICAO/IATA	Shipping Name	Paint
	Class	3
	UN No	1263
	Packaging Group	III



Material Safety Data Sheet

SAKSHI THANE 530, RAL 7038

15. Regulatory information

The following labelling information is provided in accordance with international guidelines for the labelling of hazardous substances.

Symbol(s)

Harmful

Contains;

Xylene

1,2,4-Trimethyl Benzene

1-Methoxy-2-propyl acetate

R. Phrases;

Flammable

Harmful by inhalation, in contact with skin and if swallowed

Irritating to eyes and skin

S. Phrases;

S9 – Keep container in a well-ventilated place.

S23 – Do not breathe vapour/spray.

S36/37 – Wear suitable protective clothing and gloves.

S51 – Use only in well-ventilated areas.

16. Other information

The information on this MSDS is based upon the present state of our knowledge and on current national laws. The product should not be used for purposes other than shown in the product data sheet without first obtaining written advice.

It is always the responsibility of the user to take all necessary steps to meet the demands of applicable legislation.

Copies of product data sheet are available from SAKSHI COATING PVT.LTD., on request.

DATE-25.2.2019