

## SAKSHI TC 200, PART D

## 1. Product and company identification

Product name	SAKSHI TC 200, PART D EPOXY BASED TOP COAT- FILLER
Intended use	Refer technical data sheet For Industrial use only
Application method	Brush/Roller/Spray/ Pouring
Company name	SAKSHI COATING PVT.LTD.
	Unit No.2, Opp. Mhatre Compound, Gothivali Road Rabale, Navi Mumbai – 400 701, India
Telephone No.	+91 22 6561 6751
E-mail	sakshihitech@gmail.com
Website	www.sakshihihitech.com

## 2. Composition/Information on ingredients

This product contains the following substances that present a health hazard within the meaning of the Dangerous Substances Directive and Chemical Regulation:

Ingredient	CAS No	Concentration Range%
Quartz	14808-60-7	0.1 - 1.0
TALC	014807-96-6	99+

Total may not equal 100%. The rest of the ingredients in this product are classified as non-hazardous.

# 3. Hazard identification of the product



Warning

# **Hazard Statements**

Causes skin irritation Causes serious eye irritation

May cause an allergic skin reaction

suspected of causing genetic defects

May damage fertility or the unborn child

May cause damage to organs through prolonged or repeated exposure

Toxic to aquatic life with long lasting effects



## SAKSHI TC 200, PART D

## 4. First aid measures

### Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get Medical attention.

### **Skin Contact**

Wash off immediately with plenty of water for at least 15 minutes. Get medical attention Immediately if symptoms occur.

## Inhalation

Move to fresh air. If breathing is difficult, give oxygen. Get medical attention immediately if symptoms occur.

## Ingestion

Do not induce vomiting. Obtain medical attention.

## Most important symptoms and effects

No information available.

### **Notes to Physician**

Treat symptomatically

# 5. Fire-fighting measures

### Suitable Extinguishing Media

Substance is nonflammable; use agent most appropriate to extinguish surrounding fire. Unsuitable Extinguishing Media

No information available

# 6. Accidental release measures

### **Personal Precautions**

Use personal protective equipment. Avoid dust formation. Ensure adequate ventilation.

Avoid contact with skin, eyes and clothing.

## **Environmental Precautions**

Avoid release to the environment. See Section 12 for additional ecological information.

### Methods for Containment and Cleanup

Sweep up or vacuum up spillage and collect in suitable container for disposal. Avoid dust formation.

# 7. Handling and storage

### Handling

Wear personal protective equipment. Ensure adequate ventilation. Avoid dust formation. Do not breathe dust. Avoid contact with skin, eyes and clothing.

### Storage

Keep containers tightly closed in a dry, cool and well-ventilated place.



## SAKSHI TC 200, PART D

## 8. Exposure controls and personal protection

## **Engineering measures**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapour below occupational exposure limits suitable respiratory protection must be worn.

## **Exposure Limits**

The following occupational exposure limits have been established by the Health and Safety Department. **Exposure Limits** 

The following occupational exposure limits have been established by the Health and Safety Department. TALC OSHA PEL 10 mg/m3 Total Dust

#### QUARTZ

TWA: 0.025 mg/m3as Dust

## **Respiratory Protection**

When concentrations exceed the exposure limits shown above, workers must wear appropriate approved respirators. Provision of other controls such as exhaust ventilation should be considered if practical.

### **Eye Protection**

Wear safety eyewear, e.g. safety spectacles, goggles. Eyewear should comply with an approved standard. Wear a full face shield if mixing or pouring operations pose a risk of splashes.

An eye wash station is suggested as a good working place practice.

#### **Hand Protection**

Gloves of an appropriate material should be worn during mixing and application.

#### **Skin Protection**

Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. Barrier creams may help protect areas which are difficult to cover such as the face and neck. They should however not be applied once exposure has occurred. Petroleum jelly based types such as Vaseline should not be used. All parts of the body should be washed after contact.

Hygiene measures: Avoid contact with skin, eyes and clothing.



# 9. Physical and chemical properties

Physical State Colour	Powder White
Flash Point (deg C)	N/A
Specific Gravity @ 30deg C	2.70±0.03
Vapour Density	Heavier than air
Lower Explosive Limit%	not measured
R.A.Q. to ventilate to 10% of the LEL (M3/I)	not measured
Solubility in Water	Immiscible
Viscosity (cST)	Not applicable
Odour	Specific



SAKSHI TC 200, PART D

## 10. Stability and reactivity

STABILITY — CONDITIONS TO AVOID INCOMPATIBILITY HAZARDOUS DECOMPOSITION PRODUCTS By fire: HAZARDOUS POLYMERIZATION Stable None known. None known. Carbon Dioxide, Carbon Monoxide Will not occur

# 11. Toxicological information

There are no data available on the product itself.
Information on likely routes of exposure
Inhalation May cause irritation of respiratory tract.
Eye Contac Irritating to eyes.
Skin Contact Irritating to skin. May cause sensitization by skin contact.
Ingestion - No information available.

# 12. Ecological information

There are no data available on the product itself.

The product should not be allowed to enter drains or water courses.

The product does not contain any substances classified as dangerous for the environment.

# 13. Disposal considerations

Do not allow any drains or water courses. Wastes and empty containers should be disposed of in accordance with the your local hazardous waste regulatory authority Or as per Pollution Act and Environmental Protection Act.

# 14. Transport information

Transport only in accordance with the following regulations:

### Proper shipping name:

i topoi ompping nan		
IMDG reference	UN no.:	Not dangerous goods
	Proper shipping name	Not dangerous goods
	Class:	Not dangerous goods
	Packing group:	Not dangerous goods
	EMS:	Not dangerous goods
IATA/ICAO:		
	UN no.:	Not dangerous goods
	Proper shipping name:	Not dangerous goods
	Hazard Class: Packing group:	Not dangerous goods Not dangerous goods
	-	



SAKSHI COATING PVT LTD

# **Material Safety Data Sheet**

SAKSHI TC 200, PART D

# 15. Regulatory information

The product complies with local regulations, local Pollution Control Act, Environmental Pollution Act.

# 16. Other information

Sources of key data used to compile Material safety data sheets of the ingredients.

 Data sheet:

 Prepared by:
 Safety, Health and Environmental Department, SAKSHI COATING PVT.LTD

Revision Date: 01/12/2018 Reason for revision: New Format.

The information on this MSDS is based upon the present state of our knowledge and on current national laws. The product should not be used for purposes other than shown in the product data sheet without first obtaining written advice.

It is always the responsibility of the user to take all necessary steps to meet the demands of applicable legislation. Copies of product data sheet are available from SAKSHI COATING PVT.LTD., on request.